

Fig. 822 & 922 DN50-DN300
Fig. 810 & 910 DN350-DN600
Y-Type Strainers



FEATURES & BENEFITS


- Helps to protect the system by trapping foreign matter
- Drain plug in cap as standard
- Stainless steel screen
- Test points can be fitted for system diagnostics
- ANSI versions are also available to Class 125 - Fig. 822ANSI & Fig. 922ANSI, Fig. 810ANSI & Fig. 910ANSI



MATERIAL SPECIFICATION

Part	Size	Material
Body	DN50 - DN300	Ductile Iron BS EN 1563 EN-GJS-450-10
Body	DN350 - DN400	Cast Iron EN-JL1040
Body	DN450 - DN600	Ductile Iron BS EN 1563 EN-GJS-500-7
Cover	DN50 - DN300	Ductile Iron BS EN 1563 EN-GJS-450-10
Cover	DN350 - DN400	Cast Iron EN-JL1040
Cover	DN450 - DN600	Ductile Iron BS EN 1563 EN-GJS-500-7
Screen	DN50 - DN600	Stainless Steel 304
Stud	DN50 - DN600	Steel
Nut	DN50 - DN600	Steel
Washer	DN50 - DN600	Steel
Drain Plug	DN50 - DN600	Malleable Iron
Gasket	DN50 - DN300	Fibre (Asbestos Free) Klingersil C4430
Gasket	DN350 - DN600	Graphite
Body Plug	DN50 - DN300	Malleable Iron
Body Plug	DN350 - DN600	Cast Iron EN-JL1040

DIMENSIONAL DRAWING



PRESSURE/ TEMPERATURE RATING

13 bar at 220°C
16 bar from -10 to 120°C
Note: 910 restricted to 135°C

TEST PRESSURES (HYDRAULIC)

Shell: 24 bar

SPECIFICATION

Bolted cover.
Figure 910 & 922 supplied complete with two Figure 631 test points.
Flanges to BS EN 1092-2 PN16 or ANSI B16.1 Class 125.


DIMENSIONS & WEIGHTS

Nom Size	mm	Fig. 822/922							Fig. 810/910						
		50	65	80	100	125	150	200	250	300	350	400	450	500	600
A	mm	230	290	310	350	400	480	600	730	850	960	1079	1168	1275	1450
B	mm	140	160	178	198	270	297	364	471	605	755	840	910	968	1160
C	mm	197	227	256	293	362	407	513	726	946	1150	1306	1434	1550	1858
Cover Plug	inch	1/2"	1"	1"	1 1/2"	2"	2"	2"	2"	2"	3/4"	1 1/2"	1 1/2"	1 1/2"	1 1/2"
Weight	kg	10	14	18	24	37	50	89	140	211	342	420	628	780	1080
Flow	kv	58	89	127	180	268	356	630	901	1247	2401	2969	*	*	*

*Please contact Hattersley for details

SCREEN DATA

Nom Size	mm	Fig. 822/922							Fig. 810/910						
		50	65	80	100	125	150	200	250	300	350	400	450	500	600
Hole Dia	mm	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	3	3	3	3	3
Free Flow Area/cm ²	%	32	32	32	32	32	32	32	32	32	40	40	40	40	40



Every effort has been made to ensure that the information contained in this publication is accurate at the time of publishing. Hattersley Ltd assumes no responsibility or liability for typographical errors or omissions or for any misinterpretation of the information within the publication and reserves the right to change without notice.